

Products Facts

- ✓ Concentrated gray powder
- ✓ Naturally occurring
- ✓ Archaea bacteria blend
- ✓ Organic and non toxic
- ✓ Five year+ shelf life
- ✓ Hydrophobic
- ✓ Aerobic/Facultative
- ✓ Certified pathogen FREE
- ✓ Activated by
 - fresh, salt or brackish water.
- ✓ Salinity tolerance
 - up to 24%
- ✓ Temperature range
 - 32F-120F
- ✓ pH tolerance
 - 5.5-10.0
- ✓ Not freeze dried or GMO



Works on

- ❖ Crude Oils
- ❖ Refined fuels like gasoline
- ❖ Marine fuels
- ❖ Diesel fuels
- ❖ Hydraulic Fluids
- ❖ Home Heating Oils
- ❖ Kerosene

Product /Technical Support

As the manufacturer of this product we take pride in producing a quality product. We believe that our success is due to the importance that we place on making excellent products along with our technical support of these products.

Phone 512.474.1016
Email: obitech@obio.com

Designed for use on water surfaces where oil or fuel has been spilled.



AquaZyme contains a highly concentrated blend of beneficial organic microbes packaged into an absorbent powder. Highly concentrated, safe, made from organic and natural ingredients. For superior and rapid results on water.

Contains NO GMOs or animal products.

The microbes have been selected for their large appetite to consume and convert fuels and oils, both biochemically and physically. This combination works together to quickly eliminate and destroy hydrocarbon spills on water surfaces.

For use in harbors, marinas or in oil water separators. Can also be used to control algae on water surfaces.

When AquaZyme is applied to a spill,

1. It is activated by water, non-chlorinated fresh, salt or brackish water. Once AquaZyme comes into contact with water, the microbes are activated and start working..
2. The microbes are hydrophobic and so they will stay locked into the spilled material.
3. The newer the spill the faster the cleanup time.
4. For AquaZyme to work it needs to come into direct contact with the spilled material.

Recommended Product Application Rate

Dry - 1 lb. will treat 100 sq. ft. (10×10 ft. area)

Wet - 1.lb. will treat 200 s. ft. if applied as a slurry. Add enough water as needed to spray product over area to be treated. 1 ounce per gallon of liquid is recommended.

Recommended Application Method

Dry as a sheen control:

Broadcast sprinkle enough AquaZyme onto the spill to completely cover the affected area. This locks the spilled material physically into the product. Once in contact with the spilled material the product will stay with the spill and continue to degrade the material.

Wet as a slurry:

- Add 1 oz. of product per one gallon of water and spray over the affected area. Repeat until the entire area is covered. The water used can be fresh, salt, or brackish water. The addition of water activates the product. Any waves or movement of the water will help the product to come into contact with the spilled material. The product will stay locked into the spilled material and continue to degrade and break it down.

The active ingredient in AquaZyme is the Oppenheimer Formula which is listed on the U.S. E.P.A's NCP Product Schedule. This listing does NOT mean the EPA approves, recommends, licenses, certifies, or authorizes the use of The Oppenheimer Formula on an oil discharge. This listing means only that data have been submitted to EPA as required by subpart J of the National Contingency Plan, Sec 300.915.

User must adhere to all regulations regarding hydrocarbons